

Magnetic Sign Installation & Care

Correct preparation, installation, maintenance, and storage procedures must be followed to ensure your satisfaction and to safeguard the long life of your signs and vehicle.

ACT Sign & Banner cannot be held responsible for any misapplication or misuse of signs. Due to the many variables and complex nature of automotive finishes, special care must be taken to protect your vehicle.

PREPARATION: Wash and dry vehicle. Optional step: wax vehicle surface and the back of magnetic sign prior to applying.

2A. **INSTALLATION:** Magnetic signs can only be used on smooth steel surfaces. They **CANNOT** be used on simulated wood-grain panels, fiberglass panels, panels that have been repaired with a non-steel filler (such as -Bondo), or on any corrugated or other irregular surfaces. If necessary, magnetic signs can easily be cut with a razor or X-Acto knife to work around body molding or other obstructions on the vehicle.

2B. Apply one edge of the sign to the vehicle surface in the desired location then roll the sign onto the vehicle surface until the entire sign is installed flat onto the vehicle surface. If the magnetic sign is not placed in the desired position, carefully remove by reversing the installation steps and then repeat the process. (Do not try to rearrange the sign by pulling when it is stuck magnetically onto the vehicle. This might stretch the magnetic as well as scratch the vehicle paint!)

Check area behind the magnetic material weekly and move the sign as necessary to prevent any discoloration or clouding of the automotive clear coat.

Note: A magnetic sign should never be applied to a newly painted vehicle. Allow at least 60 days for fresh paint to cure.